

MAXIMA K 5W-30

Full-Synthetic Gasoline Motor Oil



Description

This is new-generation motor oil, which is formulated with synthetic base oils and special additives, and which produced for vehicle motors containing DPF and SCR and having emission-reducing systems.

Applications

Maxima K 5W-30 for diesel passenger and light commercial vehicle motors equipped with DPF and SCR exhaust emission systems demanding motor oil with an ACEA C2 or C3 performance level and gasoline vehicle motors with catalytic converters. This is specially developed for KIA branded vehicles.

Benefits

- Ensures high motor performance.
- Extends the life of the exhaust emission systems.
- Contributes to the low emission production and protects the environment.
- Reduces the generation of the residue and dropping and ensures the motor to remain clean.
- Helps the fuel saving.

Performance

API SP/CF, ACEA C2/C3

Typical Specifications*

| | | |
|---------------------------------------|------------|-------|
| SAE Viscosity Grade | | 5W30 |
| Density, 15 °C, kg/liter | ASTM D4052 | 0,860 |
| Flash Point, COC, °C | ASTM D92 | 220 |
| Viscosity, 40 °C, mm ² /s | ASTM D445 | 74,7 |
| Viscosity, 100 °C, mm ² /s | | 11,80 |
| Viscosity Index | ASTM D2270 | 165 |
| Pour Point, °C | ASTM D97 | -36 |

* Values shown may differ between productions.



Petrol Ofisi

Renewed Maxima with Adaptech technology provides full protection in all conditions.