

AVISTA peer EVO ATF 3000

High-grade automatic transmission oil of the AVISTA peer EVO line meeting the Dexron III-H specification, as well as many OEM approvals. The product is field-tested for application where Dexron II and GM Motors Type A Suffix A (TASA) is recommended.

APPLICATION

- Automatic transmissions
- The product is red coloured.

CHARACTERISTICS / APPLICATION BENEFITS

- High-stable viscosity index
- very low flow point
- very good oxidation stability
- well adapted friction coefficients
- neutral behaviour by inhibition to non-ferrous metals

APPROVALS

DTFR	13C170 (MB 236.9) 13C100 (MB 236.1)
MAN	MAN 339 Typ L-1 / V-1 / Z-1
ZF	ZF TE-ML 03D, 04D, 14A, 17C (ZF004774)

SPECIFICATIONS

GM	Dexron III-H
Ford	Mercon
Voith	55.6335.xx

RECOMMENDATIONS

Allison	C-4 TES-389
Caterpillar	TO-2
Renk Doromat	Renk Doromat
Volvo	97341
ZF	ZF TE-ML 11B

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 306		75W
Density @ 15 °C	DIN EN ISO 12185	g/cm ³	0.830 – 0.870
Kin. Viscosity @ 100 °C	ASTM D7279	mm ² /s	7.5 – 8.5
Brookfield @ -40 °C	DIN 51398	mPa*s	max. 20.000
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. -54

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 11)